
BESSER ENHANCED ADJUSTABLE BOX CULVERT FORM

Rubber gasketed adjustable box culvert equipment provides producers with the ultimate in flexibility. The size of the form can be increased and decreased to produce a wide range of product sizes to meet market requirements. Reducing your inventory of forms, producing products to exacting dimensions and improving employee safety during production process are significant benefits of using Besser forms for producing Box Culverts.



Integral Locking System remove a <u>common fail</u>



Discover the Besser Difference

Typical Adjustable Core, Pallet and Header Assembly (core top not shown)

Typical Header Extension available in 1', 2' and 3' lengths (6" length optional)

Double Adjustable Cast Steel and Fully CNC Machined Header Assembly 6" or 8" wall standard (optional header wall spacers available)

Typical Wall Spacer Extension available in 1', 2' and 3' lengths (6" length optional)

Enhanced Design Double
Adjustable Basic Core Corner
common basic sizes 4' x 2',
6' x 3' and 9' x 4' for dry cast
production method (custom
sizes available upon request)

Typical Pallet Extension available in 1', 2' and 3' lengths (6' length optional) (optional)

Optional Bolt-On Cast Steel Fully CNC Machined Header Wall Spacers (available for 7", 7-1/2", 10" and 12" slab/wall thickness production)

Adjustable Header Haunches

Adjustable Core Haunches (optional)

Core Extension available in standard 1', 2', 3', 4', 5' and 6' widths (6" wide optional)

Adjustable Pallet Haunches (optional)

Double Adjustable Cast Steel and Fully CNC Machined Universal Pallet Corner

300 mm | 350 mm

Typical Mold Dimensions for Besser Adjustable Box Culvert Molds with Enhanced Design													
Basic Size	Typical Maximum	Dry Cast Form Strip	Dry Cast Static Cast	Wet Cast	6" Haunch	8" Haunch	12" Haunch	Adjustable Haunch	4' Length	6' Length	8' Length	Minimum Wall	Maximum Wall
3' x 2'	8' x 8'	Х	Х		Х						Х		8″
4' x 2'	8' x 8'	X	X			χ		Х			X		8″
4' x 3'	8′ x 8′	X	X	Χ		X		**			X		8″
6' x 3'	12' x 12'	X	X	Χ			χ	Х	X	X	X	8″	12"
9' x 4'	12' x 12'	Х	Х	Х			X	Х	Х	X	Х	10"	12"
9' x 4'	20' x 12'	Х	X	χ			χ	Х	Х	X		10"	12"
Metric siz	es available												

350 mm

Your Besser Sales Representative can provide the configurations available for these sizes



1 m x 1 m | 4.5 m x 4.5 m | X

111 S. George Street Sioux City, Iowa 51103 USA +1.712.277.8111 sales@besser.com NOTE: The "minimum wall" shown is for the production of precast box culverts with ASTM C1677 rubber gasket joints. Standard ASTM C1433 and ASTM C1577 TS, BS and SW thickness is available for the production of mastic joint box culvert elements.

For better viewing, all guards, safety devices and signs are not necessarily shown. Some of the equipment shown or described throughout this brochure is available at extra cost. Besser Company reserves the right to change or improve product design and specifications without prior notice. Since the time of printing, some of the information in this brochure may have been updated, ask your Besser sales representative for details.

^{*} Basic Size is the smallest product size that can be produced on this mold set

^{**} Not available for wet cast mold equipment